

GREASE WAREHOUSE

POWER SYNTHETIC OIL 15W-40

It is a high-performance synthetic technology lubricant. for diesel engines that helps extend engine life in severe on- and off-highway applications. (Recommended for Ecuador 15,000 km.) The advanced chemistry of These products provide exceptional performance in modern engines, including those with Exhaust Gas Recirculation (EGR) systems, as well as older engines running on low or high content fuels of sulfur.

POWER SYNTHETIC OIL 15W-40 is recommended for use in a wide range of heavy duty applications and in the operational environments found in manufacturing industries transportation, both in trucks operating at high speeds and long distances, as in urban service buses, with frequent starts and stops. These products will provide a exceptional protection in most of the demanding diesel engines of Caterpillar, Cummins, Detroit Diesel, Mack, Mercedes Benz, Navistar, Volvo, and others. Also Complies with API SM specification for gasoline engines and mixed fleets.

Quality standards:

Meets or exceeds:

POWER SYNTHETIC OIL 15W-40

conserving API SP and Manufacturers ILSAC GF-6A service classification.

- ACEA E9, A3/B3
- DHD-1

- MB 228.3

- Navistar International
- MAN M3477

-Volvo VDS-4

- Mack EO-O PP

- Cummins CES 20081

- DD 93K218

-Caterpillar ECF-3

- DEUTZ III-05

-VW 505

- SCANIA LDF-2

- ISUZU DEO

-Renault Trucks

RLD-2

Health and security:


This product does not represent a danger to the health or safety when used properly in the recommended application.

Avoid contact with skin, Check the sheet health and safety, for more information.

Storage:

If possible, store under roof. The product should not be stored at temperatures greater than 60°C, exposed to the sun or freezing.

PARAMETER	ASTM METHOD	SAE 15W-40 CJ-4
Cinema viscosity ca @40 C	D 445	112.55
Cinema viscosity ca @100 C	D 445	fifteen
Viscosity Index	D 2270	139
Density @ 15C Kg/l	D 4052	0.8469
Pour Point, C	D 97	-27
Flash Point, C	D 92	230
TBN, mg/KOH/g	D 2896	10
Sulfated ashes, % weight	D 874	1.1



516S 25th W Ave, Tulsa, Ok 74127 USA